

ZHV-0837L Solenoids Valve



总重量 Total Weight: 155g
应用范围: 用于按摩枕、按摩床等
APPLICATION: Massage pillow, Massage bed

综合特性 GENERAL FEATURES

- 常用压力: 300mmHg
In common use pressure: 300mmHg
- 使用压力范围: 0 ~ 380mmHg
Use pressure range: 0 ~ 300mmHg
- 密封件: 丁腈橡胶, 硅橡胶
Working pressure: Nbr, Mvq
- 寿命: 最小工作100万次
Wrok Life: Work 1 million Min.
- 漏气量: 小于12mmHg/30Sec
Air-leakage volume: Less than 12mmHg/30Sec

类型: 二位三通 TYPE: Two way two port

单位:mm Units:mm

类型: 二位三通 TYPE: Two way three port

单位:mm Units:mm

COIL DATA线圈资料

$\text{Duty cycle (\%)} = \frac{\text{"ON" time}}{\text{"ON" time} + \text{"OFF" time}} \times 100\%$			Continuous (100%)	Or less (50%)	Or less (25%)	Or less (10%)
$\text{工作周期 (\%)} = \frac{\text{工作时间}}{\text{工作时间} + \text{断开时间}} \times 100\%$			连续 (100%)	间断 (50%)	间断 (25%)	间断 (10%)
MAX. "on" time in seconds 最大工作时间 (秒)			1800	1800	1800	
Watts at 20°C 瓦特数 (在20°C)			3.1	3.5	4.4	
Ampere-turns at 20°C 安匝值 (在20°C)			582	642	667	
Type no.	Resistance (20°C) Ω ±10%	No. Turns	VoltS DC 电压			
型号	阻值 (Ω) ±10%	线圈匝数				
ZHC-0630L	3200	18600	100			
	3500	20400	110			
	9000	30000	200			

ZHV